

METHOD FOR VERIFYING THE IDENTITY OF A PASSENGER

Field of the Invention

This invention relates to a method for verifying the identity of a passenger, more particularly the invention involves printing a human-
5 cognizable image of the passenger on a conveyance ticket so as to facilitate rapid and repeated security verification.

Background of the Invention

Concerns over the ever-increasing sophistication of terrorism and drug trafficking have prompted transportation networks to utilize increased security
10 procedures, in order to keep pace. Traditional security protocols dictate heightened security perimeters surrounding sensitive areas, as one approaches those areas. For example, the sensitive area of an airport is the aircraft itself. While runways and secure aircraft service areas are protected by a badge and uniform system by which only authorized personnel are permitted access to
15 various secure areas, this system is not amenable to controlling aircraft access by passengers. Current security doctrine involves allowing access to airport terminals to the public upon passing a metal detector screening. Upon presenting a ticket and perhaps a form of photo-identification, a passenger is issued a boarding pass which designates the flight particulars of the passenger.
20 The issuance of a boarding pass may occur on either side of the metal detection screening. The present system fails in that there are no means available to verify whether the passenger presenting a boarding pass upon gaining access to the aircraft, is in fact the passenger of record. In this way, the secure nature of the aircraft to only authorized passengers is compromised.

25 The weaknesses of the conventional security systems in regard to the presentation of a boarding pass by a person other than the passenger of record are not practically solved with existing methods. The addition of a passenger identification checkpoint using picture identification at the point of gateway embarkation is not feasible, owing to the time-consuming nature of a
30 checkpoint. A checkpoint procedure under ideal conditions requires about thirty seconds per passenger and results in delays in loading the aircraft. This

process is further slowed by passengers fumbling for picture identification stored in baggage, purses, wallets and the like. Thus, there exists a need for a method of verifying a passenger's identity at the time of boarding the transport that does not involve the use of a separate piece of picture identification.

5 Security at airports, passenger ships, train and bus stations, as well as other central transportation sites is a concern for all who utilize conveyances such as airplanes, trains and buses. Various systems are utilized to verify the identity of a passenger prior to boarding such a conveyance. For example, the identity of the passenger is typically verified at the time the ticket is purchased,
10 at the time the boarding pass is issued or during passenger check-in. Because the identity of a passenger is not typically verified after the purchase of the ticket or after the issuance of the boarding pass, there is an opportunity for a ticket purchased by one passenger to be utilized by another passenger. Thus, there remains a need for a simple system which will permit the verification of
15 the identity of a passenger at the time of boarding the particular conveyance.

Summary of the Present Invention

A process for encoding an access pass with an image of an authorized user to facilitate identity verification includes the steps of verifying the identity of the user beyond a security perimeter and taking electronic image of the user
20 with a camera capable of generating a computer-storage image output. A human-cognizable image of the user is then printed directly onto the access pass.

An access pass system for verifying the identity of the user includes a self-supporting access pass having machine readable data series as either a bar
25 code encoding a reference number or a magnetic strip encoding a reference number. A computer database stores a user image associated with the reference number. A video display coupled to the computer database and a machine data reader adapted to read the data series operates such that upon reading the data series a human-cognizable user image is displayed on the
30 video display.

The process for encoding an access pass with an image of the user to facilitate identity verification includes verifying the identity of the user beyond a security perimeter and taking electronic images of the user with a camera capable of generating a computer-storable image output. A data series is encoding onto an access pass either with a bar code or magnetic strip. The data series for instance the computer-storable image output within a computer. Upon reading the data series from the computer database, a human-cognizable image of the user is recalled from the computer-storable output in reference to the data series within said computer database. A human-cognizable image is displayed on a video display interfaced with the computer database. Comparison of the human-cognizable image of the video display with the user presenting the access pass then occurs.

Brief Description of the Drawing

Figure 1 depicts an embodiment of a conveyance ticket of the instant invention; and

Figure 2 depicts a flowchart of operative steps of an embodiment of the instant invention for verifying the identity of a passenger through the printing of a human-cognizable image on a boarding pass.

Detailed Description of the Invention

The instant invention is discussed herein in reference to passenger aircraft transportation, not as a means of limitation, but rather is intended to be exemplary of the invention utility. One skilled in the art will readily appreciate the applicability of the instant invention to passenger identification in the transportation contexts illustratively including: cruise ships, ski-lifts, rail- and bus-lines.

Upon purchase of a conveyance ticket or at the time travel arrangements are made, the identity of the passenger is verified and an electronic image of the purchasing passenger is taken, with a device capable of generating an electronic image. Alternatively, the passenger identity is verified upon check in at the transportation site. Illustratively, devices capable of

generating an electronic image 23 of Figure 2 include charged coupled device (CCD) arrays and video analog camera/video frame grabber systems.

5 The electronic image is input to a printer which prints a human-cognizable image of the passenger 24 onto a boarding pass 10 which is depicted in Figure 1. Any dissimilarity between the person requesting a boarding pass and the passenger of record thus becomes obvious to the issuing agent by visual comparison of the printed image 2 and the person requesting the pass. Upon a passenger presenting a conveyance ticket, a boarding pass of the instant invention is then issued. Owing to relatively low quality of the
10 image 2, such as a 256 gray scale image, the printing of the human-cognizable image does not significantly decrease the speed at which an agent distributes passes. It is appreciated that a higher quality image in terms of gray scale tones or color is also operative herein. In printing a human-cognizable image onto a boarding pass, it is recognized that the ink is non-smudgeable to prevent
15 obscuring the image through handling.

In an alternate embodiment, the human-cognizable passenger image is printed with an ink color, or alternatively a background color, that corresponds to a specific departure. Thus, an additional security mechanism is provided to assure that an individual passenger is boarding the correct departing aircraft.
20 With a variety of ink colors and patterns, aircraft personnel are able to discern whether a given passenger is attempting to board their designated transport. The direct printing of a human-cognizable image onto a boarding pass thereby affords heretofore unavailable security measures. The passenger image is stored electronically within a computer storage. Preferably, the image is stored
25 in any conventional image storage format within a central database.

The association of passenger image data within the central database and passenger travel data affords a transport agent the ability to verify passenger identity at the time of boarding independent of an actual boarding pass. Thus, a passenger appearing for transport departure absent a boarding pass and
30 identification is granted transport access on the basis of accessing central database stored image and travel data. The present invention also affords

advantages in the event of a catastrophic accident in speeding up the identification of dead and injured passengers. Preferably, the information on the travel itinerary 4 of the passenger is also printed onto the boarding pass at this time. It is further appreciated that a conveyance ticket itself is amenable to use as a substrate for the printing of a human-cognizable image of the instant invention, especially in instances where a boarding pass separate from the ticket is not issued.

An additional human-cognizable image 6 may be printed on the boarding pass, thus enabling an image to be printed on passes having several separable portions. The retention of a portion of the pass having the passenger's image thereon optionally allows for additional verification stages following boarding.

The boarding pass substrate 12 is generally composed of a semi-rigid rectilinear portion of paper or cardboard. Preferably, the substrate 12 has a perforation line 14 transecting the substrate. The substrate being printed with a blank conveyance form (not shown). The form is formatted to accept individualized travel itinerary details 4 of the passenger within blank sections thereof. The individualized travel datum illustratively including: passenger name, passenger destination, transport designation, departure time, arrival time, seat assignment, travel class, transport tariff and the like. In particular to aircraft transport the details may include flight number and meal selection information. A portion of the blank form being open for the printing of the human-cognizable image of the passenger.

The passenger then proceeds to the boarding site with the boarding pass. At the time of boarding, or upon arrival at the boarding site, the human-cognizable image on the boarding pass is compared with the passenger presenting the boarding pass 25 to ensure that the passenger who purchased the ticket is the same passenger who is boarding the conveyance.

The security of the transport is enhanced by passenger verification occurring at the time of boarding. The identity verification method of the instant invention is considerably quicker than that using picture identification

because the verifying agent merely glances at the face of the passenger and their presented boarding pass.

In a preferred embodiment, the electronic image of the passenger is associated with the travel arrangements of the passenger 26 and stored in a centralized database 27. The database storage of a passenger image with travel arrangements provides for subsequent security monitoring 28 and for the tracking of criminal suspects traveling with counterfeit identification. Furthermore, image data coupled with travel itinerary data is optionally utilized outside of a security setting to provide demographic passenger information, for targeting transport promotional offers, and verification of non-transference of special fares and benefits extended to particular passengers.

In an alternative embodiment, the human-cognizable electronic image, and other individualized travel details, illustratively including: passenger name, passenger destination, departure time, arrival time, seat assignment, travel class, transport tariff, et al., are electronically associated to a unique alphanumeric code, printable in alphanumeric and in bar code format.

All pertinent text-based individualized travel details then are printed upon the boarding pass, along with the unique alphanumeric code, in alphanumeric and bar code format. Upon boarding, or at any other prior or subsequent security checkpoint, the bar code is read with a bar code scanner, which then causes the individualized travel details to be referenced, and the human-cognizable digital image to be displayed upon a video screen interfaced with the bar code scanner at the security checkpoint. This image is then compared with the individual presenting the boarding pass.

The unique alphanumeric code also is provided in alphanumeric format to enable manual entry of the code in the event of difficulty reading the printed bar code. It is appreciated that the alphanumeric and bar code formatted information is optionally printed in duplicate on separable portions of the boarding pass.

In an alternate embodiment, all pertinent text based individual travel details then are printed upon the boarding pass along with a machine readable

data series in the form of a magnetic strip. The magnetic strip encoding the unique alphanumeric code. Upon boarding, or at any other prior or subsequent security checkpoint, the magnetic strip is passed through a machine reader thereby causing the individualized travel details to be referenced and the human-cognizable digital image of the passenger to be displayed on a video display interfaced with the magnetic strip reader at the security checkpoint. The video display image is then compared with the individual presenting the boarding pass.

In still another embodiment, the camera taking the image of the passenger may directly apply the image to the boarding pass by using either photosensitive material in at least a portion of the boarding pass in a Polaroid-type system or by directly transferring the electronic image created by a digital camera to the boarding pass.

One skilled in the art will readily appreciate that the present invention is well adapted to carry out the objects and provide the applications mentioned, as well as those inherent therein. Modifications and variations within the spirit of the invention will occur to those skilled in the art. Such modifications are also intended to fall within the scope of the appended claims.

What is claimed is: